1	I CLAIM:
2	1. A cargo carrier comprising:
3	a frame having a front edge with a trailer hitch
4	connection;
5	a left and a right jack assembly;
6	each said jack assembly having a riser body; and said
7	frame having a left and a right edge each having
8	a jack connecter assembly for removable
9	attachment to the respective riser body.
10	
11	2. The cargo carrier of claim 1, wherein the left and
12	right jack assemblies each have a caster, thereby enabling
13	the jack assemblies to be connected to the frame and to roll
14	the frame in and out of a vehicle's receiving hitch.
15	
16	3. The cargo carrier of claim 1 wherein the jack
17	connector assemblies each comprise a bracket longitudinally
18	alignable with the respective left and right edge of the
19	frame, said bracket having a quick disconnect mechanism to
20	the frame edge.
21	
22	4. The cargo carrier of claim 3, wherein each quick
23	disconnect mechanism is a locking pin received thru both the
24	frame and the bracket.
25	

- 1 5. The cargo carrier of claim 4, wherein the frame
- 2 further comprises a square tube construction, and the
- 3 bracket has a C shape to engage a side of the square tube.

- 5 6. The cargo carrier of claim 3, wherein the left and
- 6 right jack assemblies each further comprise a caster.

7

- 8 7. The cargo carrier of claim 3, wherein the trailer
- 9 hitch connection further comprises a removable male hitch
- 10 shaft which is adapted to fit into a vehicle hitch, and the
- 11 frame further comprising a receiving hitch tube, thereby
- 12 enabling the male hitch shaft to be connected to the vehicle
- 13 hitch and then receive the receiving hitch tube in a loading
- 14 operation of the frame onto the vehicle.

15

- 16 8. The cargo carrier of claim 1, wherein the frame
- 17 front edge further comprises a left and right stabilizer bar
- 18 protruding forward for contact with a vehicle bumper.
- 9. A cargo carrier comprising:
- a frame having a front edge with a trailer hitch
- 21 connection; and
- 22 said frame having a left and a right edge each with a
- removable connector for removable attachment to a jack.
- 24 10. A cargo carrier comprising:

1	a frame having a front edge with a trailer hitch
2	connection;
3	a left and a right jack assembly;
4	each said jack assembly having a riser body;
5	said frame having a left and a right edge each having
6	a jack connector assembly for removable
7	attachment to the respective riser body; and
8	wherein the jack connector assemblies each comprise a
9	bracket longitudinally alignable with the
10	respective left or right edge of the frame, said
11	bracket having a quick disconnect mechanism to
12	\mathcal{N} the frame edge.
13	
14	11. The cargo carrier of claim 1, wherein the jack
15	connector assembly further comprises a vertical column
16	mounted to the left and the right edge of the frame, said
17	vertical column having a male connector to receive a female
18	connector on the jack assembly.
19	
20	12. A cargo carrier comprising: a frame having a front
21	edge with a trailer hitch connection; a left and a right
22	jack assembly; each said jack assembly having a riser body;
23	said frame having a left and a right edge each having a jack
24	connector assembly for removable attachment to the removable

attachment to the respective riser body; and wherein the

- 1 jack connector assembly further comprises a vertical column
- 2 mounted to the left and the right edge of the frame, said
- 3 vertical column having a male connector to receive a female
- 4 connector on the jack assembly.

- 6 13. A cargo carrier comprising; a frame means
- 7 functioning to support a cargo box; said frame means having
- 8 a front edge with a trailer hitch means functioning to
- 9 connect to a vehicle hitch; a left and a right jack assembly
- 10 means functioning to lift the frame means to a level for
- 11 mounting to the vehicle hitch; said frame means having a
- 12 left and a right edge means each having a jack connector
- 13 means functioning to removably connect to the jack assembly
- 14 means.

15

- 16 $\sqrt{}$ 14. The cargo carrier of claim 13, wherein the left and
- 17 the right jack assemblies each further comprise a wheel
- 18 means functioning to enable the frame and cargo box to be
- 19 rolled to and from the vehicle hitch.

20

- 21 15. The cargo carrier of claim 14, wherein the trailer
- 22 hitch means further comprises a removable male hitch shaft
- 23 means functioning to attach to the vehicle hitch and to a
- 24 frame female shaft receiver, thereby enabling the cargo box

1	and frame to be rolled into the removable male hitch shaft
2	when it is mounted to the vehicle hitch.
3	
4	16. The cargo carrier of claim 15 wherein the front
5	edge further comprises a left and a right stabilizer means
6	functioning to contact the vehicle under load and reduce
7	movement of the frame means.
8	
9	